

STONE[®] CCTV Power Distribution Cabinet



Product Description

1. AC input voltage suitable for the world,
2. Max power: 72W,
3. Output voltage: 12V
4. Output current: 5A & 10A
5. Adjustable & multiple outputs: 1CH input for 4CH output
6. Application: CCTV security power supply

		PARAMETER		
		MODEL		
		TX07	TX08	
Input	Input voltage	AC100-240V,50/60Hz		
	Output connector	4channel	8 channel	
Output	Max power	72W	120W	
	Output voltage	DC12V(adjusted max 13.8V)		
	Ripple wave	(mVp-p): <1%		
	Linear modulate	±0.5%max		
	Temperature coefficient	±0.02%/°C		
	Start time	≤3s(240VAC output,1o=100%)		
	Guard time	≥20ms(240VAC input,1o=100%)		
	Output standard	12V5A,9-CH output	12V10A,9-CH output	
	Protection	Override protection	115%~200%kvA,automatic recovery	
		Short-circuit protection	1 channel: automatic recovery	
Insulation	Insulation strength	1500VAC/10mA,1MIN		
	Insulation resistance	≥30MΩ,DC 500V		
Environment	Working temperature	0°C~40°C,10%~90%RH		
	Store temperature	-20°C~60°C,10%~90%RH		
Size	Size	190x170x63mm		
	Weight	1080G	1080G	