

STONE® HD Varifocal IR Bullet Camera

2.0 Megapixel Resolution Camera



Model: HD1080IRVF2812



Features

1/3" 2.0 Megapixel CMOS
 25/30/50/60fps@1080P
 High speed, long distance real-time transmission HD and standard definition switch.
 OSD Menu, control over coaxial cable (Option) Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
 Max. IR LEDs length 30m, Smart IR
 IP66, DC12V

Supreme HD Megapixel Camera

Technical Specifications

Mode	PAL	
VIDEO		
Image Pick-up Device	1/3" 2.0 Megapixel CMOS	
Effective Pixels	1984(H) × 1225(V)	
Noise Reduction	3D/2D	
	525 Lines / 60 Fields / 30 Frames	625 Lines / 50 Fields / 25 Frames
Synchronisation	Internal / Line Lock	Internal / Line Lock
Frequency	15,734 kHz (H) 59.94 Hz (V)	15,625 kHz (H) 50 Hz (V)
Video Frame Rate	25/30/50/60fps 720P; 25/30fps 1080P	
Min. Illumination IR LED	0.01Lux@F1.2(AGCON),0Lux IR on 36 LED IR Distance 20 meters Max	
Video Output	1-channel BNC HD high definition video	
OPERATIONAL		
OSD	Option	
WDR	Option	
Gain Control	Auto	
White Balance	Auto ATW / AWC / Manual (1,800°K ~ 10,500°K)	
Electronic Shutter Speed	Auto (1/60 ~ 1/120,000) Flicker less	Auto (1/50 ~ 1/120,000) Flicker less
Operating Temp / Humidity	-10 °C ~ +50 °C / 20 % ~ 80 % RH	
Storage Temp / Humidity	-20 °C ~ +60 °C / 20 % ~ 80 % RH	
Power Source	Wide Voltage 12 Vdc – 16VDC	
Power Consumption	Max. 1.0 W	
MECHANICAL		
Dimensions (L X W X H)	180mmx 60 mm x 60mm	
Weight	180 g	
Lens Mount	2.8mm – 12mm VF lens	