


STONE® 4/8/16ch High Definition DVR



Features

- Up to 4/8/16 cameras with 1080p real-time preview
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- All channel synchronous playback, GRID interface & smart search
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS

1080P Resolution

ANYTIME, ANYWHERE

You could log in the app to watch the video of anywhere you want to as long as your smart phone or tablet is connected to Internet.



Specification:

Model		HD-004	HD-008	HD-1600
Main Processor		Embedded processor		
Operating System		Embedded LINUX		
Input		4 channel, BNC	8 channel, BNC	16 channel, BNC
Standard		NTSC(525Line, 60f/s), PAL(625Line, 50f/s)		
Input		4 channel, BNC		
Output		1 channel, NC		
Two-way Talk		Reuse audio input/output channel 1		
Interface		1 HDMI, 1 VGA, 1 BNC		
Resolution		1920×1080, 1280×1024, 1280×720, 1024×768, 800×600		
Display Split		1/4	1/4/8/9	1/4/8/9/16
Privacy Masking		4 rectangular zones (each camera)		
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Video/Audio Compression		H.264 / G.711		
Resolution		1080P(1920×1080)/720P(1280×720/1280×600)/960H(960×576/960×480)/D1 /4CIF(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)		
Record Rate	Main Stream:	1080P/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)		
	Extra Stream	CIF/QCIF(1~25/30fps)		
Bit Rate		48~6144Kb/s		
Record Mode		Manual, Schedule(Regular(Continuous), MD), Stop		
Record Interval		1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips		
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank		
Alarm Input		4 channel	8 channel	16 channel
Sync Playback		1/4	1/4/8	1/4/8/16
Search Mode		Time/Date, MD & Exact search (accurate to second)		
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Backup Mode		USB Device / Network		
Ethernet		RJ-45 port (10/100M/1000M)		
Network Functions		HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter		
Max. User Access		128 users		
Smart Phone		iPhone, iPad, Android, Windows Phone		
Internal HDD		2 SATA port, up to 8TB		
USB Interface		2 ports(1 Rear), USB2.0		
RS232		1 port, For PC communication & Keyboard		
RS485		1 port, For PTZ control		
Power Supply		DC12V/5A		
Power Consumption		15W(without HDD)		
Working Environment		-10 ~+55℃ / 10~90%RH / 86~106kpa		
Dimension(W×D×H)		1U, 375mm×285mm×45mm		
Weight		2.35KG(without HDD)		