

STONE[®] iFace 302 Face Recognition & Fingerprint Reader



- Power Button
- Pin Hole for Reset
- Slot for USB Memory Device

Features

- Elegant German-designed casing
- 4.3" TFT color touch screen display
- Supports 50 time zones, 99 groups and 10 unlock combinations for access control
- Contact relay for door locks, exit button, alarm, bell, etc.
- Face / Fingerprint / Pin Password Reader
- Infra-red light source enables face detection and matching in dimly lit environment
- 6 user-defined function keys
- Contactless 1-second employee recognition
- Operates stand-alone or with any 26-bit
- Wiegand 3rd party access control panel
- Voice and visual indicates for acceptance and rejection of valid and invalid fingerprints/faces
- Multi-language support
- SDK available for OEM customers and software developers

Specifications

Capacity		Verification/Identification	
Face	400 templates	Face Identification	<= 2 sec
Fingerprints	2000 templates	Face Verification	<= 1 sec
Transaction	100,000	Fingerprint Matching	1:N to 2000 templates
		Fingerprint Verification	<= 1 sec
		Fingerprint Identification	<= 2 sec
Display		Communication	
LCD	4.3 in touch screen	Port	RS232/485
		Port	Ethernet 10/100M
		Port	USB-HOST
		Port	Wiegand Output
Power		Environment	
Oper. Voltage	12V DC, 3A	Oper. Temp	32°-105°F (0°-42°C)
		Oper. Humidity	20%-80%
Dimensions		Options	
Height	165.2mm/6.5 inches	Option	GPRS/WiFi
Width	193.6mm/7.6 inches	Option	Serial Printer
Depth	86mm/3.4 inches	Option	Mifare / iClass (Pending)
		Option	Proximity card
		Option	Backup Battery
Part Numbers		Packing Information	
iFace302	Proximity Reader	Box Size	10 x 12 x 4.5 in / 25 x 30 x 12 cm
iFace 302-Mifare	iFace 302 with Mifare	Weight	4 lbs / 64 oz
iFace 302-HID	iFace302 with HID reader		